

PROPORTIONAL 4-WAY CONTROL VALVES SOLENOID OPERATED


HD2-PS-*

20 l/min 32 MPa (320 bar)

1 DESCRIPTION

Valves HD2-PS are proportional directional control valve with subplate mounting interface acc. to ISO 4401, DIN 24340 (CETOP 03).

The design of the body is an high quality five chamber casting. The valve is available with different spools able to control different flow ranges. In the standard version, the valve housing is phosphated for 240 h salt spray protection acc. to ISO 9227.



2 ORDERING CODE

(1)	(2)	(3)	(4)	(5)	(6)
HD2	-	PS	-	-	/ 10

(1) HD2: 4-way directional valve Cetop 02 – Pressure 32 Mpa (320 bar)

(2) PS : Proportional electric control

(3) Functional spool type (see [4]):

-number is the main spool type

1: closed center (P, A, B, T blocked)

3: P blocked, A, B, T connected

-spool nominal flow

P : 12 l/min with $f_iP = 1$ MPa (10 bar) (PA+BT or PB+AT)

R : 8 l/min with $f_iP = 1$ MPa (10 bar) (PA+BT or PB+AT)

O4 : 04 l/min with $\Delta P = 1$ MPa (10 bar) (PA+BT or PB+AT)

D : differential $Q_b = 2Q_a$: 8/4 l/min with $\Delta P = 1$ MPa (10 bar))

-letter is the solenoid or spring arrangement:

C : 2 solenoids, spool is springs centred

ML : 1 solenoid ("a") spool is centred + 1 end position

MLb : 1 solenoid ("b") spool is centred + 1 end position

(4) Options and variants:

K : extended manual overrides (see [7])



ZC : zinc plated valves (see [8])

(5) Type of coil and supply voltages

R2 : R= 5 Ω standard for V12DC;fl

R4 : R=21 Ω standard for V24DC;fl

(6) Design number (progressive) of the valve.




The spool 12 shifts in to the valves body 11 subject to the action of springs 13 and proportional solenoid 1. Spool 12, depending from its shape and its position in the valves body 11, opens and/or closes passages between P, A, B, T ports, thus controlling the direction and the rate of the hydraulic flow. Solenoid 1 is energized by electric current flowing-in through cables; in case of electric cut-offs, the spool can be manually shifted by acting on the emergency pins 5, located at the end of the solenoids and accessible through the retaining nuts 10.

3 TECHNICAL DATA


Nominal flow rates	4, 8, 12 l/min	Electric Characteristics: Valves type HD2-PS-* are operated by proportional solenoids. The values of nominal max. current are: for coils type R2 (5 Ω): I max = 1,7 A R4 (21 Ω): I max = 0,8 A Currents to hydraulic proportional valves are normally supplied by an electronic driver based on PWM mode of operation, capable of full control of min and max values of current for drivers type UED-M15
Maximum nominal pressure (P,A,B)	32 MPa (320 bar)	
Maximum pressure at T port	16 MPa (160 bar)	
Maximum rec. Pressure drops	10 MPa (100 bar) see [8]	
Protection DIN 40050	IP 67	
Duty cycle	100%	
Service life	$\geq 10^7$ cycles	
Installation and Dimensions	(see [10])	
Mass	Approx 1,0 / 1,4 kg.	

4 SPOOL IDENTIFICATION & NOMINAL FLOW RATE


Nominal Flow rate 4 l/min




Nominal Flow rate 8 l/min



Nominal Flow rate 12 l/min




Differential flow: $Q_b = 2Q_a$ (example $P \rightarrow B = 8$ l/min and $A \rightarrow T = 4$ l/min)



5 TYPICAL DIAGRAMS


Typical flow curves of valves HD2 – PS - *, with spools type P, R, 04 – see 1, in standard configuration measured with mineral oil at 36 cSt and at 50°C at $\Delta P = 0.1$ Mpa (10 bar) for flow $P \rightarrow B \rightarrow A \rightarrow T$



6 FLOW RATES AND PRESSURE DIFFERENTIAL

For a given ΔP on a given valve the flow rates are proportional to the driving current (see 4); for a given driving current on a given valve, the flow rates increase with the increasing of the ΔP up to certain limits.

Typical limit curves are:



Solenoid current:

- 1 = 50%
- 2 = 60%
- 3 = 70%
- 4 = 80%
- 5 = 90%
- 6 = 100%

